

## WHITHWORTH FEINGEWINDE BS 84

Gewinde- bezeichnung	Durchmesser Inch	Durchmesser außen mm	Durchmesser Kernloch mm	Gänge je Inch	Steigung mm	Kernloch- bohrer mm
<b>BSF 3/16"</b>	3/16	4,763	3,747	32	0,794	3,90
<b>BSF 7/32"</b>	7/32	5,556	4,394	28	0,907	4,70
<b>BSF 1/4"</b>	1/4	6,350	5,100	26	0,977	5,40
<b>BSF 9/32"</b>	9/32	7,142	5,893	26	0,977	6,00
<b>BSF 5/16"</b>	5/16	7,938	6,459	22	1,154	6,60
<b>BSF 3/8"</b>	3/8	9,525	7,899	20	1,270	8,30
<b>BSF 7/16"</b>	7/16	11,113	9,304	18	1,411	9,70
<b>BSF 1/2"</b>	1/2	12,700	10,668	16	1,587	11,10
<b>BSF 9/16"</b>	9/16	14,288	12,256	16	1,587	12,70
<b>BSF 5/8"</b>	5/8	15,875	13,549	14	1,814	14,10
<b>BSF 11/16"</b>	11/16	17,463	15,137	14	1,814	15,70
<b>BSF 3/4"</b>	3/4	19,050	16,336	12	2,117	17,00
<b>BSF 13/16"</b>	13/16	20,637	17,93	12	2,12	18,5
<b>BSF 7/8"</b>	7/8	22,225	19,269	11	2,309	20,0
<b>BSF 15/16"</b>	15/16	23,81	20,85	11	2,31	21,0
<b>BSF 1"</b>	1	25,400	22,148	10	2,540	23,0
<b>BSF 1 1/8"</b>	1 1/8	28,575	24,963	9	2,822	26,0
<b>BSF 1 1/4"</b>	1 1/4	31,750	28,138	9	2,822	29,0
<b>BSF 1 3/8"</b>	1 3/8	34,925	30,861	8	3,175	32,0
<b>BSF 1 1/2"</b>	1 1/2	38,100	34,036	8	3,175	35,0
<b>BSF 1 5/8"</b>	1 5/8	41,275	37,211	8	3,175	38,0
<b>BSF 1 3/4"</b>	1 3/4	44,450	39,802	7	3,628	41,0
<b>BSF 2"</b>	2	50,800	46,152	7	3,628	47,0
<b>BSF 2 1/4"</b>	2 1/4	57,150	51,730	6	4,233	52,0
<b>BSF 2 1/2"</b>	2 1/2	63,500	58,080	6	4,233	58,5
<b>BSF 2 3/4"</b>	2 3/4	69,850	64,430	6	4,233	65,0
<b>BSF 3"</b>	3	76,200	69,692	5	5,080	70,0
<b>BSF 3 1/4"</b>	3 1/4	82,550	76,042	5	5,080	76,5
<b>BSF 3 1/2"</b>	3 1/2	88,900	81,670	4,5	5,644	82,0
<b>BSF 3 3/4"</b>	3 3/4	95,250	88,020	4,5	5,644	88,5
<b>BSF 4"</b>	4	101,600	94,370	4,5	5,644	95,0

